ZASŁAW

Agricultural trailers ZASLAW AGRO

AGRO

Agricultural trailer
ZASŁAW D737-6
6 TONS

Agricultural trailer
ZASŁAW D-737
8 TONS

Agricultural trailer
ZASŁAW D-737
10 TONS

Agricultural trailer
ZASŁAW D-737
12 TONS long

Agricultural trailer
ZASŁAW D-737
14 TONS

TECHNICAL PARAMETERS OF TURNTABLE TRAILERS

	D-737BA-6	D-737BA-6 for pallets	D-737BA-8	D-737BA-10	D-737AA-12	D-737AA-12	D-737AA-14
Maximum gross weight [kgs]	9500	9500	11200	14300	17000	17000	18000
Load capacity	6000	6000	8000	10000	12000	12000	14000
Cubature (m^3)	8,5	8,7	10,8	13,1	15,2	15,2	17,6/20,1
Internal length of box body (mm)	4040	4500	4500	4500	4500	5200	5200
Internal width of box body (mm)	2126	2420	2420	2420	2420	2420	2420
Height [mm]	2014	2170	2170	2670	2840	2650	2850/3050
Total length [mm]	6192	6990	6990	6990	6990	7650	7650
External width [mm]	2250	2550	2550	2550	2550	2550	2550
Drop sides height [mm]	500+500	800	500+500	600+600	600+800	600+600	800+600/ 800+800
Loading body height [mm]	1014	1170	1170	1380	1380	1390	1390
Wheel size	11,5/80-15,3	400/60R15,5	400/60R15,5	385/65R22.5	385/65R22.5	385/65R22.5	385/65R22.5
Tipper kind	3 – side	3 – side	3 – side	3 – side	3 – side	3 – side	3 – side
Wheelbase (mm)	1500	1800	1800	1800	1800	2040	2040

AGRO

TECHNICAL PARAMETERS OF TANDEM TRAILERS

	D-762-10	D-762-12k	D-762-12	D-762-14
Maximum gross weight [kgs]	14500	16500	17000	19000
Load capacity	10000	12000	12000	14000
Cubature (m^3)	13,1	15,2	15,2	17,6/20,1
Internal length of box body [mm]	4500	4500	5200	5200
Internal width of box body [mm]	2420	2420	2420	2420
Height [mm]	2670	2870	2650	2850/3050
Total length [mm]	6570	6570	7250	7250
External width [mm]	2550	2550	2550	2550
Drop sides height [mm]	600+600	600+800	600+600	800+600/ 800+800
Loading body height [mm]	1380	1380	1390	1390
Wheel size	385/65R22.5	385/65R22.5	385/65R22.5	385/65R22.5
Tipper kind	3 – side	3 – side	3 – side	3 – side
Wheelbase [mm]	1800	1800	2040	2040

Agricultural trailer
ZASŁAW D-762-10
10 TONS

Agricultural trailer
ZASŁAW D-762-12k
12 TONS

Agricultural trailer
ZASŁAW D-762-14
14 TONS

Agricultural trailer
ZASŁAW D-762
12 TONS

AGRO

Agricultural trailer
ZASŁAW D-744
9 TONS

Agricultural trailer
ZASŁAW D-744
13 TONS

Agricultural trailer
ZASŁAW D-745
14 TONS

Agricultural trailer
ZASŁAW D-746
20 TONS

TECHNICAL PARAMETERS OF AGRO TRAILERS DEDICATED FOR BALES TRANSPORT

	D-744-9	D-744-13	D-745-14	D-745-16	D-746-20
Maximum gross weight [kgs]	11500	16000	18500	20500	24000
Load capacity	9000	13000	14300	16200	20000
Platform area (m^3)	17,4	17,4	24(25,9)	24(25,9)	24(25,9)
Internal length of box body [mm]	7200	7200	9920+800	9920+800	9920+800
Internal width of box body [mm]	2420	2420	2420	2420	2420
Height [mm]	3350	3350	3422	3422	3422
Total length [mm]	9297	9297	12558	12558	12558
External width [mm]	2550	2550	2550	2550	2550
Ladder height [mm]	1800	1800	1800	1800	1800
Loading body height [mm]	1140	1140	1170	1170	1240
Wheel size	500/50R17	385/55R19.5	500/50R17	500/50R17	385/55R19.5
Wheelbase [mm]	1800	1800	2000	2000	2000

AGRO

TECHNICAL PARAMETERS OF HALF PIPE TRAILERS

	D-764- 21 1R	D-764- 21 1B
Maximum gross weight [kgs]	21000	21000
Load capacity	15000	15500
Cubature (m^3)	24/33	15
Internal length of box body [mm]	7200	5500
Internal width of box body [mm]	2260	2200
Height [mm]	3120/3725	2550
Total length [mm]	9810	8065
External width [mm]	2550	2510
Drop sides height [mm]	1570(+600)	1200
Loading body height [mm]	1550	1350
Wheel size	550/60R22.5	500/60R22.5
Tipper kind	Rear chute	Rear chute
Wheelbase [mm]	2000	2000

Agricultural trailer
ZASŁAW D-764-21 1R
21 TONS

Agricultural trailer
ZASŁAW D-764-21 1B
21 TONS

DOLLY TROLLEY
ZASŁAW 385/65R22,5

DOLLY TROLLEY
ZASŁAW 265/70R19,5

TECHNICAL PARAMETERS OF DOLLY TROLLEYS

	Dolly 1	Dolly 2
Maximum gross weight [kgs]	9000	9000
Load capacity [at speed 105km/h]	7800	7800
Empty mass (kgs)	1200	1200
Maximum speed (km/h)	105	105
Total length [mm]	3943	4176
Total width [mm]	2404	2510
Maximum height of truck fifth wheel coupling[mm]	1200	1200
Minimum height of truck fifth wheel coupling [mm]	1100	1150
Wheel size	265/70 R19,5 twin	385/65R22.5
Wheelbase [mm]	1240	1740
Drawbar eye height [mm]	865	865
Drawbar length [mm]	2693	2760

AGRO

Curtainsider trailer
ZASŁAW D-744F
12 TONS

Curtainsider trailer
ZASŁAW D-746F
19 TONS

TECHNICAL PARAMETERS OF CURTAINSIDER TRAILERS

	D-744F	D-745F	D746F
Maximum gross weight [kgs]	16000	18500/20500	24000
Load capacity	12000	14300/16200	19000
Cubature (m^3)	47,91	66	66
Internal length of box body [mm]	7200	9920	9920
Internal width of box body [mm]	2420	2420	2420
Height [mm]	3350	4000	4000
Total length [mm]	9297	12558	12558
External width [mm]	2550	2550	2550
Internal height [mm]	2750	2750	2750
Loading body height [mm]	1140	1170	1240
Wheel size	500/50R17	500/50R17	385/65R22,5
Wheelbase [mm]	1800	2000	2000

Curtainsider trailer
ZASŁAW D-745F
16 TONS

AGRO

UNIQUE SOLUTIONS FOR ZASŁAW™ TRAILERS

Hydraulic supporting leg:
The possibility of establishing of hydraulic supporting leg as an additional option for tandems.

Frame with pinned wires:
All the wires are pinned and leading by technological holes in the frame, automatic control of braking force valve in standard option.

Drawbar type Y:
Drawbar type Y with pulling power 120kN with holder for cables is available in standard option with all the turntable trailers.

Dropside lock with logo:
Forged hinges of dropsides, 6 pcs for trailers with 4,5 m of box body length and 8 pcs for trailers with 5,2 m of box body length. Hooks of central locking are placed with angle such that rear close first, and then front.

Sealing:
Dropsides are sealed by flexible seal and additionally by barstock to the floor from the inside which prevent breaking of seals by hard materials.

BPW suspension up to 60 km/h
Possibility of setting up BPW axles up to 60 km/h with parabolic suspension as an additional option both in trailers and tandems.

AGRO

UNIQUE SOLUTIONS FOR ZASŁAW™ TRAILERS

Pipe bells with roll stop:
Pipe bell under tipping balls on rear part with roll stop and Teflon liner, preventing bouncing and making noise of box body while driving.

Tipping bolts with different diameters:
There are two bolts for locking of box body while tipping with different diameter, cross matching to prevent of box body length and dent floor.

Mudguards, box and tank:
All the trailers with maximum gross weight over 10 tons, have mudguards behind first and second axle, toolbox with wheel wrenches and warning triangle and water tank in standard equipment as well as new tires.

Bumper, pillars and lamp cover:
Foldable rear bumper with possibility of disassembling, rear lamps protected by metal grille, rear pillars screwed, as well as middle (possibility of disassembling top boards or all of them to have a platform without boards and pillars).

Agro frame:
Solid frame made of I-beam. In trailers 8-12 ton thickness of the lower belt is 8 mm as well as top belt stringer. Thickness of middle belt is 4 mm. The height of frame is 338 mm. In trailers 12-14 ton thickness of the lower belt is 12 mm as well as top belt stringer. Thickness of middle belt is 5 mm. The height of frame is 338 mm.

Agro tarpaulin:
Handles to hold tarpaulin mounted on string(fold itself). After folding, tarpaulin doesn't cover box body of the trailer. Rack tarpaulin pipe is mounted on the arm enabling change position during loading(it doesn't block loading body). There is possibility of mounting from both sides of rack.

CONTACT:
Tel: +48 516 00 49 39
e-mail: zaslaw@zaslaw.eu
www.zaslaw.eu

ZASŁAW™ The European Trailer Company
ul. Krakowska 140
34-120 Andrychów
GPS: N 55.90620, E 37.43602